

Claims:

1. Method for producing a strip-like pre-material from metal by means of rollers (11, 12) of a roll stand (2), which define a roll gap (13), by rolling the metal strip in two or more than two rolling steps,
characterised in that the metal strip (16) is rolled discontinuously in successive steps between the same two rollers (11, 12), for which purpose the metal strip (16) is recalled, after such a section of the metal strip (16) has been rolled, and the recalled section is rolled once again, the recalled section of the metal strip (16) being selected to be shorter than the circumference of the rollers (11, 12).
2. The method as defined in Claim 1, **characterised in that** the metal strip (16) is rolled also during the recalling step.
3. The method as defined in Claim 1 or 2, **characterised in that** the length of the recalled sections of the metal strip (16) is selected to be maximally equal to half the circumference of the rollers (11, 12).
4. The method as defined in Claim 1, 2 or 3, **characterised in that** the two rollers (11, 12) are selected to have a cylindrical shape.
5. The method as defined in any of the preceding claims, **characterised in that** the last rolling step in each of the recalled sections of the metal strip (16) is carried out between circumferential segments of the two rollers (11, 12) that have not yet acted on the respective section of the metal strip (16) in the one or more preceding rolling steps.

6. The method as defined in Claim 5, **characterised in that** step-by-step repeated rolling of the respective section of the metal strip (16) is carried out in such a way that of the circumferential segments of the two rollers (11, 12) that act on the respective section of the metal strip (16), the circumferential segment of the two rollers (11, 12) that acts on the respective section of the metal strip (16) in the first step has carried out the greatest number of rolling steps, and the circumferential segment of the rollers (11, 12) that acts on the respective section of the metal strip (16) in the last rolling step has carried out the smallest number of rolling steps.
7. The method as defined in Claim 6, **characterised in that** the smallest number is selected to be zero.
8. The method as defined in Claim 5, 6 or 7, **characterised in that** the shell surface of the two rollers (11, 12) is reworked to restore the original surface quality when a predetermined number of rolling steps has been reached by those circumferential segments with which the smallest number of rolling steps has been carried out.
9. The method as defined in Claim 8, **characterised in that** the predetermined number of rolling steps is adjusted to the desired surface quality of the strip-like pre-material.
10. The method as defined in any of the preceding claims, **characterised in that** by rolling the metal strip (16) it is simultaneously equalised.

11. The method as defined in any of the preceding claims, **characterised in that** proofs for coins and medals are produced from the pre-material.
12. The method as defined in any of the preceding claims, **characterised in that** the profile is rolled into the metal strip (16) by sections, the profile extending over the full width of the metal strip (16) and having a metal-strip thickness (16) varying over the length of the metal strip (16).
13. The method as defined in Claim 12, **characterised in that** a periodically recurring profile is rolled into the metal strip (16).
14. The method as defined in any of the preceding claims, **characterised in that** the rollers (11, 12) and the metal strip (16) are accelerated and braked in the respective rolling steps in synchronism and to the same degree.
15. The method as defined in any of Claims 1 to 3, 10 and 12 to 14, **characterised in that** for producing a strip-like pre-material with a profile recurring in successive sections of the pre-material, a roll stand (2) is used which permits the height of the roll gap (13) to be varied, and that the sections of the metal strip (16) to be profiled are passed through the roll gap (13) in recurring steps of predetermined lengths (21) until the depth of the desired profile of the pre-material has been reached in the respective section of the metal strip (16).
16. The method as defined in Claims 12 to 15, **characterised in that** a profile is rolled into the recalled section of the metal strip (16) in two or more than two rolling steps.

17. The method as defined in Claims 12 to 16, **characterised in that** the profile is rolled into the metal strip (16) from above.
18. The method as defined in Claims 12 to 16, **characterised in that** the profile is rolled into the metal strip (16) from below.
19. The method as defined in Claims 12 to 16, **characterised in that** a profile is rolled into the metal strip (16) from above and from below.
20. The method as defined in Claims 12 to 19, **characterised in that** the metal strip (16) is merely reduced in thickness, but not yet profiled, in a first rolling step.
21. The method as defined in Claim 20, **characterised in that** the metal strip (16) is equalised in the first rolling step.
22. The method as defined in Claim 20 or 21, **characterised in that** the reducing step is followed by one or more profiling steps between the same two rollers (11, 12).
23. The method as defined in Claim 20, 21 or 22, **characterised in that** the length (L2) of the reducing step is greater than the length (L1) of the next following profiling step.
24. The method as defined in any of Claims 20 to 23, **characterised in that** the metal strip (16) is recalled, following the reducing step, by a length smaller than the length (L2) of the reducing step and greater than the length (L1) of the next following profiling step in the same section of the metal strip (16).

25. The method as defined in any of Claims 12 to 24, **characterised by** the use of a roll stand (2) in which at least one of the two rollers (12) comprises in its shell surface a profiled segment (35, 40) with a contour which, in combination with the contour of the other roller (11), defines the roll gap (13).
26. The method as defined in Claim 25, **characterised in that** prior to rolling a profile, the metal strip (16) is first equalised in the roll gap (13) between the same rollers (11, 12) in steps of a length (L2) not smaller than the length (L1) of the first profiling step, with moderate reduction in thickness, is then recalled by a step equal to at least the length (L1) of the first profiling step and maximally equal to the second length (L2), whereafter the profile is rolled into the recalled section of the metal strip (16),
and that the rollers (12) for equalising the metal strip (16) comprise on their shell surface a cylindrical circumferential segment (36) which is separated, if necessary, from the profiled circumferential segments (35, 40) that exhibit a non-cylindrical contour.
27. The method as defined in any of Claims 12 to 26, **characterised in that** one roller (12) of the roll stand (2) is displaced during the rolling process of the metal strip (16) for varying the height of the roll gap (13).
28. The method as defined in Claim 27, **characterised in that** the upper or the lower roller (11, 12) are selectively displaced during the rolling process.

29. The method as defined in Claim 27, **characterised in that** the respective roller (11, 12) is displaced by means of a servo drive (32, 34, 44).
30. The method as defined in Claim 29, **characterised in that** one or two electric motors (34) or one or two short hydraulic cylinders are used for the servo drive.
31. The method as defined in any of Claims 27 to 30, **characterised in that** the displacement of the roller (12) is effected by means of a programme-controlled drive (32, 33, 34, 44), the profile to be produced in the respective rolling step being stored in a programme-controllable control unit (43) as control curve for the drive (32, 33, 34, 44) which effects the displacement of the roller (12).
32. The method as defined in any of Claims 27 to 31, **characterised in that** one of the rollers, specifically the upper roller (12), has a notch (45) parallel to its axis.
33. The method as defined in any of the preceding claims, **characterised in that** the two rollers (11, 12) are driven step by step and in synchronism with the feeding motion of the metal strip (16).
34. The method as defined in any of the preceding claims, **characterised in that** the two rollers (11, 12) are differently rotated during the recalling action of the metal strip (16).
35. The method as defined in any of Claims 15 to 32, **characterised in that** a relieved portion (37, 38, 39) is provided in the shell surface of the

rollers (11, 12), between the circumferential segments (35, 36, 40) effective during the rolling process, which relieved portion extends over a circumferential angle such that the next following circumferential segment (35, 36, 40) to become active during the rolling process will cut into the metal strip (16) only after the preceding circumferential segment of the metal strip (16), active during the rolling process, has released the metal strip (16).

36. The method as defined in any of the preceding claims in combination with Claim 11 or 25, **characterised in that** the thickness of the metal strip (16) is reduced during the equalising step by a dimension in the order of one tenth of the thickness.
37. The method as defined in any of the preceding claims, **characterised in that** the metal strip (16) to be rolled is unwound from a first coiler (5) and the rolled metal strip (16) is wound up on a second coiler (6), and that the rotational speed of the rollers (11, 12) and the circumferential speed of the second coiler (6) are mutually matched, especially in the phase when the rollers (12, 13) cut into the metal strip (16).
38. The method as defined in any of the preceding claims, **characterised in that** cutting-in by a roller (12) is effected at reduced rotational speed of the roller (12) and, correspondingly, reduced feeding speed of the metal strip (16) and that the movements are then accelerated.
39. The method as defined in Claims 1 to 36, **characterised in that** the metal strip (16) is recalled using a first pair of grippers (52).

40. The method as defined in Claim 39, **characterised in that** the metal strip (16) is advanced by the first pair of grippers (52) also for rolling.
41. The method as defined in Claim 39 or 40, **characterised in that** the metal strip (16) is pulled, during rolling, by a second pair of grippers (53) engaging that section of the metal strip (16) that exits from the roll gap (13).
42. The method as defined in any of the preceding claims, **characterised in that** a tensile strength is constantly maintained in the metal strip (16), during rolling just as during the recalling action.
43. The method as defined in any of the preceding claims, **characterised in that** the width of the metal strip (16) is selected in such a way that two or more than two of the objects, that are intended to be punched out from the pre-material formed by rolling, can be punched out one beside the other.
44. Use of a device having a roll stand (2) with two rollers (11, 12) that define a roll gap (13) the height of which can be varied, and with a recalling device (5, 52) for a metal strip (16) to be rolled, arranged on the run-in end of the roll gap (13),

for producing a strip-like pre-material from metal, with a profile which recurs in successive sections of the pre-material, according to the method defined in Claim 12,

for which purpose the first (11) and/or the second roller (12) are provided on their shell surface with two or more than two circumferential

segments (35, 36, 40), following each other in the circumferential direction, which are not all of them equal in contour, and for which purpose a drive motor (7, 54) is provided for the recalling device (5, 52) arranged on the run-in end of the roll gap (13), for recalling the metal strip (16) by steps of predeterminable length.

45. The use of a device as defined in Claim 44, wherein the recalling device is a first coiler (5).
46. The use of a device as defined in Claim 44, wherein the recalling device is a gripper feed mechanism (52).
47. The use of a device as defined in any of Claims 44 to 46, wherein a pulling device (6, 53) for the strip-like pre-material is provided on the run-out end of the roll gap (13).
48. The use of a device as defined in Claim 47, wherein the pulling device is a second coiler (6) for winding up the strip-like pre-material.
49. The use of a device as defined in Claim 47, wherein the pulling device is a second gripper feed mechanism (53).
50. The use of a device as defined in any of Claims 44 to 49, wherein the two rollers (11, 12) can be driven one independently from the other.
51. The use of a device as defined in any of Claims 44 to 50, wherein at least one roller (11, 12) has a cylindrical circumferential segment (36).
52. The use of a device as defined in Claim 51, wherein both rollers (11, 12) have a cylindrical circumferential segment (36).

53. The use of a device as defined in any of Claims 44 to 52, wherein the roll stand (2) is designed as equalising rolling mill.
54. The use of a device as defined in any of Claims 44 to 53, wherein the drive motor (7, 52) for the recalling device (5, 52) provided on the run-in end of the roll gap (13) is an electric servomotor.
55. The use of a device as defined in any of Claims 44 to 54, wherein the pulling device (6, 53) provided on the run-out end of the roll gap (13) is driven by an electric servomotor (8, 55).
56. The use of a device as defined in any of Claims 44 to 55, wherein the two rollers (11 and 12) are each loaded on their side facing away from the roll gap (13) by one supporting roller (14, 15) whose roll necks (25) are pre-stressed in their roll neck bearings (26) for reducing their bearing play.
57. The use of a device as defined in any of Claims 44 to 55, wherein the first roller (11) and the second roller (12) are not loaded by supporting rollers, but rather the roll necks (21, 22) of the first roller (11) and of the second roller (12) are pre-stressed in their roller neck bearings (22) for reducing their bearing play.
58. The use of a device as defined in any of Claims 44 to 47, wherein the first and the second rollers (11, 12) are discontinuously driven in a manner such that they are driven, during the strip feed, in synchronism with the pulling device (6, 53) provided on the run-out end of the roll gap (13), whereas they are temporarily stopped and/or positioned individually or jointly by forward or reverse rotation when the recalling

device (5, 52) provided on the run-in end of the roll gap (13) is driven in the reverse sense for recalling the metal strip (16).

59. The use of a device as defined in any of Claims 44 to 58, wherein the circumferential speed of the two rollers (11, 12) and the speed of the pulling device (6, 53), preferably also the speed of the recalling device (5, 52) can be controlled in arbitrary fashion.
60. The use of a device as defined in any of Claims 44 to 59, wherein one of the two rollers (12, 13), preferably the upper roller (12), can be moved up and down in controlled fashion during the rolling process.
61. The use of a device as defined in Claim 60, wherein the one or the other roller (11, 12) can be selectively moved up and down in controlled fashion during the rolling process.
62. The use of a device as defined in Claim 60 or 61, wherein one or more servo drives (32, 33, 34, 44) are provided for effecting the displacement of the respective roller (11, 12).
63. The use of a device as defined in Claim 62, wherein the servo drives (32, 33, 34, 44) comprise one electric motor (34) or one or two short hydraulic cylinders each.
64. Use of a device having a roll stand (2) with two rollers (11, 12) that define a roll gap (13) the height of which can be varied, and with a recalling device (5, 52) for a metal strip (16) to be rolled, arranged on the run-in end of the roll gap (13),

for producing a strip-like pre-material from metal, with a profile which recurs in successive sections of the pre-material, according to the method defined in Claim 12,

for which purpose one of the two rollers (11, 12) can be moved up and down in the roll stand (2) in controlled fashion during the rolling process, by a distance determined by the desired profile, in response to the feeding motion of the metal strip (16),

and for which purpose a drive motor (7, 54), specifically a servomotor, is provided for the recalling device (5, 52) arranged on the run-in end of the roll gap (13), for recalling the metal strip (16) by steps of predeterminable length.

65. Use of a device having a roll stand (2) with two rollers (11, 12) that define a roll gap (13),
and with a recalling device (5, 52) for a metal strip (16) to be rolled, arranged on the run-in end of the roll gap (13),

for producing a strip-like pre-material from metal with high surface quality, according to the method defined in Claim 1,

for which purpose a drive motor (7, 54), specifically a servomotor, is provided for the recalling device (5, 52) arranged on the run-in end of the roll gap (13), for recalling the metal strip (16) by steps of predeterminable length.

66. The use of a device as defined in Claim 64 or 66, wherein a pulling device (6, 53) for the strip-like pre-material is provided on the run-out end of the roll gap (13).

67. The use of a device as defined in Claim 64, 65 or 66, wherein the recalling device is a first coiler (5).
68. The use of a device as defined in Claim 64, 65 or 66, wherein the recalling device is a gripper feed device (52).
69. The use of a device as defined in Claim 66, wherein the pulling device is a second coiler (6) for winding up the strip-like pre-material.
70. The use of a device as defined in Claim 66, wherein the pulling device is a second gripper feed mechanism (53).
71. The use of a device as defined in any of Claims 60 to 70, wherein a servomotor (8, 55) is provided also for the pulling device (6, 53) provided on the run-in end of the roll gap (13).
72. The use of a device as defined in Claim 71, wherein an electric control unit (43) is provided in which the displacement of the one roller (12) required for an intended profile is, preferably, digitally stored as curve and wherein the servomotors (7, 8; 54, 55) of the recalling device (5, 52) and of the pulling device (6, 53), one or two servomotors (41, 42) for rotating the two rollers (11, 12), and one or more actuating drives (32, 33, 34) for the displaceable roller (12) coupled with an incremental rotary transducer (44), are connected to said control unit (43).
73. The use of a device as defined in any of Claims 59 to 72, wherein the sense of rotation of the two rollers (11, 12) can be reversed for rolling in both directions.

74. The use of a device as defined in any of Claims 50 to 57, wherein the displaceable roller (11) has a notch (45) parallel to its axis.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000